

SUZUKI PERFORMANCE NOTEBOOK

Lake Walloon , MI

Suzuki Marine

Test Date: 8/5/19

Test Boat: Avalon CCF

Boat Type: Tri-Log Pontoon

Test Motor: DF200ATL



BOAT	ENGINE	OTHER SPECS
------	--------	-------------

<table style="width:100%;"> <tr> <td style="width: 20%;">Material</td> <td>Aluminum</td> </tr> <tr> <td>Length</td> <td>25' 5"</td> </tr> <tr> <td>Beam</td> <td>8' 6"</td> </tr> <tr> <td>Weight (Dry)</td> <td>2450 lbs</td> </tr> <tr> <td>Maximum HP</td> <td>250 hp</td> </tr> <tr> <td>Fuel Capacity</td> <td>38 gallons</td> </tr> <tr> <td>Transom Height</td> <td>20"</td> </tr> <tr> <td>Steering</td> <td>SeaStar Hyd</td> </tr> </table>	Material	Aluminum	Length	25' 5"	Beam	8' 6"	Weight (Dry)	2450 lbs	Maximum HP	250 hp	Fuel Capacity	38 gallons	Transom Height	20"	Steering	SeaStar Hyd	<p style="text-align: center;">Suzuki</p> <table style="width:100%;"> <tr> <td style="width: 20%;">Engine Type</td> <td>DOHC 16 Valve</td> </tr> <tr> <td>HP</td> <td>200 hp</td> </tr> <tr> <td>Displacement</td> <td>2867 CC</td> </tr> <tr> <td>Operating Range</td> <td>5500-6100 rpm</td> </tr> <tr> <td>Weight</td> <td>498 lbs</td> </tr> <tr> <td>Lubrication</td> <td>Wet Sump</td> </tr> <tr> <td>Fuel Delivery</td> <td>Multi Point EFI</td> </tr> <tr> <td>Ignition</td> <td>Solid State</td> </tr> </table>	Engine Type	DOHC 16 Valve	HP	200 hp	Displacement	2867 CC	Operating Range	5500-6100 rpm	Weight	498 lbs	Lubrication	Wet Sump	Fuel Delivery	Multi Point EFI	Ignition	Solid State	<p style="text-align: center;">Propeller</p> <table style="width:100%;"> <tr> <td style="width: 20%;">Material</td> <td>Stainless Steel</td> </tr> <tr> <td>Diameter/Pitch</td> <td>16" X 18.5"</td> </tr> <tr> <td>Number of Blades</td> <td>3</td> </tr> </table> <p style="text-align: center;">Mounting Height</p> <table style="width:100%;"> <tr> <td style="width: 20%;">Hole Position</td> <td>Flat on Transom</td> </tr> <tr> <td>Jack Plate</td> <td>N/A</td> </tr> </table>	Material	Stainless Steel	Diameter/Pitch	16" X 18.5"	Number of Blades	3	Hole Position	Flat on Transom	Jack Plate	N/A
Material	Aluminum																																											
Length	25' 5"																																											
Beam	8' 6"																																											
Weight (Dry)	2450 lbs																																											
Maximum HP	250 hp																																											
Fuel Capacity	38 gallons																																											
Transom Height	20"																																											
Steering	SeaStar Hyd																																											
Engine Type	DOHC 16 Valve																																											
HP	200 hp																																											
Displacement	2867 CC																																											
Operating Range	5500-6100 rpm																																											
Weight	498 lbs																																											
Lubrication	Wet Sump																																											
Fuel Delivery	Multi Point EFI																																											
Ignition	Solid State																																											
Material	Stainless Steel																																											
Diameter/Pitch	16" X 18.5"																																											
Number of Blades	3																																											
Hole Position	Flat on Transom																																											
Jack Plate	N/A																																											

PERFORMANCE DATA	TEST CONDITIONS
------------------	-----------------

RPM	MPH	GPH	MPG	RANGE											
IDLE	2.5	0.4	6.25	214	<table style="width:100%;"> <tr> <td style="width: 20%;">Water Conditions</td> <td>Medium Chop</td> </tr> <tr> <td>Wind Velocity</td> <td>10 to 15 mph</td> </tr> <tr> <td>Air Temperature</td> <td>84 degrees</td> </tr> <tr> <td>Fuel Load</td> <td>20 gallons</td> </tr> <tr> <td>Weight Onboard</td> <td>2 persons Full Safety Gear</td> </tr> </table>	Water Conditions	Medium Chop	Wind Velocity	10 to 15 mph	Air Temperature	84 degrees	Fuel Load	20 gallons	Weight Onboard	2 persons Full Safety Gear
Water Conditions	Medium Chop														
Wind Velocity	10 to 15 mph														
Air Temperature	84 degrees														
Fuel Load	20 gallons														
Weight Onboard	2 persons Full Safety Gear														
1000	4.1	0.7	5.86	200											
1500	5.9	1.3	4.54	155											
2000	8.3	1.9	4.37	149											
2500	10.9	2.9	3.76	129											
3000	15.9	3.6	4.42	151											
3500	19.4	4.9	3.96	135											
4000	22.7	6.7	3.39	116											
4500	26.6	8.8	3.02	103											
5000	31.3	11.1	2.82	96											
5500	35.4	15.1	2.34	80											
6000	40.2	18.3	2.20	75											

Results may vary. Range based on 90% fuel capacity.

PERFORMANCE SUMMARY

Top Speed	40.2 MPH
0-20 Acceleration	4.8 seconds
Optimum Cruising Range	@ 3000 RPM 151 Miles
Best Cruising	@ 3000 RPM
Fuel Efficiency	4.42 MPG

FOR MORE INFORMATION, CONTACT:

Avalon Pontoon Boats
Alma, MI 48801
(989) 463-2112

www.avalonpontoon.com

Suzuki Marine
www.suzuki.com

