

SUZUKI PERFORMANCE NOTEBOOK

Syracuse, IN

Suzuki Marine

Test Date: 8-16-17

Test Boat: Bennington Pontoon

Boat Type: Pontoon

Test Motor: Suzuki DF350ATX



BOAT		ENGINE		OTHER SPECS	
2018 28 RSRX1		Suzuki DF350ATX		Propeller	
Material	Aluminum	Engine Type	4-Stroke V-6	Material	Stainless
Length	28' 4" (3 pontoons)	HP	350	Diameter/Pitch	15.50 x 19.5
Beam	10' (elipticle pontoons)	Displacement	4.4L	Number of Blades	6 (twin 3 Blade)
Weight	4960 lb.s est. w/arch	Operating Range	5700-6300		Contra-Rotation
Maximum HP	400	Weight	727 lb.s	Mounting Height	
Fuel Capacity	83 gallons	Lubrication	Wet Sump	Hole Position	3rd Hole Up
Transom Height	25"	Fuel Delivery	Multi-Point EFI	Jack Plate	N/A
Steering	Hydraulic w/PA	Ignition	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
RPM	MPH	GPH	MPG	RANGE	Water Conditions	Light Chop
IDLE	2.7	0.5	5.40	403	Wind Velocity	5-7 MPH
1000	4.4	0.9	4.89	365	Air Temperature	75
1500	6.4	1.7	3.76	281	Fuel Load	40
2000	8.2	2.4	3.42	255	Weight Onboard	2 persons
2500	10.4	3.7	2.81	210		Full Safety Gear
3000	16.7	5.5	3.04	227		Arch w/Bimini (up)
3500	21.2	7.9	2.68	200	PERFORMANCE SUMMARY	
4000	24.9	10.3	2.42	181	Top Speed	44.1 MPH
4500	30.0	14.1	2.13	159	0-30 Acceleration	5.9 seconds
5000	35.5	18.5	1.92	143	Optimum Cruising	@ 3000 RPM
5500	39.5	23.0	1.72	128	Range	227 Miles
6000	43.5	28.6	1.52	114	Best Cruising	@ 3000 RPM
6300	44.1	29	1.52	114	Fuel Efficiency	3.04 MPG
Results may vary. Range based on 90% fuel capacity.						

FOR MORE INFORMATION, CONTACT:

Bennington Pontoon Boat, LLC
 Elkhart, IN 46517
 benningtonmarine.com
 888-906-2628

Suzuki Marine
 www.suzuki.com

