

SUZUKI PERFORMANCE NOTEBOOK

Red Wing, MN

Suzuki Marine

Test Date: 8-6-19

Test Boat: Premier Marine

Boat Type: Pontoon

Test Motor: Suzuki DF40ATL



BOAT		ENGINE		OTHER SPECS	
200 Sunspre		Suzuki DF40ATL		Propeller	
Material	Alm.	Engine Type	Inline 3	Material	Alm
Length	20' 5"	HP	40 hp	Diameter/Pitch	11.25x9
Beam	8' 6"	Displacement	941 CC	Number of Blades	3
Weight	1850 lb.s	Operating Range	5000-6000 RPM	Mounting Height	
Maximum HP	115	Weight	229 lbs	Hole Position	2nd Hole Up
Fuel Capacity	31 gallons	Lubrication	Wet Sump	Jack Plate	N/A
Transom Height	20	Fuel Delivery	Multi-Point EFI		
Steering	Cable	Ignition	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
RPM	MPH	GPH	MPG	RANGE	Water Conditions	Smooth
IDLE	2.2	0.1	22.0	614	Wind Velocity	0
1000	2.4	0.1	24.0	670	Air Temperature	78 degrees
1500	3.7	0.2	18.5	516	Fuel Load	25 gallons
2000	4.6	0.4	11.5	321	Weight Onboard	2 persons
2500	5.4	0.7	7.7	215		Full Safety Gear
3000	6.4	0.9	7.1	198	PERFORMANCE SUMMARY	
3500	7.5	1.1	6.8	190	Top Speed	17.4 mph
4000	9.1	1.5	6.1	169	0-30 Acceleration	N/A seconds
4500	11.4	1.7	6.7	187	Optimum Cruising	187 Miles
5000	14.4	2.2	6.5	183	Range	@ 4500
5500	16.4	3.3	5.0	139	Best Cruising	6.7 MPG
5850	17.4	3.8	4.6	128	Fuel Efficiency	@ 4500 RPM

Results may vary. Range based on 90% fuel capacity.

FOR MORE INFORMATION, CONTACT:

Premier Marine, Inc.
26612 Fallbrook Ave.
Wyoming, MN 55092
www.pontoons.com

Suzuki Marine
714-996-7040
www.suzuki.com

