

SUZUKI PERFORMANCE NOTEBOOK

Orange Beach, AL
Test Boat: Silverwave

Suzuki Marine
Boat Type: Tri-Toon

Test Date: 8-17-19
Test Motor: Suzuki DF200ATX



BOAT	ENGINE	OTHER SPECS
------	--------	-------------

SW5 2410 JS Tritoon		Suzuki DF200ATX		Propeller	
Material	Aluminum	Engine Type	4-Stroke Inline 4	Material	Stainless
Length	23' 10"	HP	200	Diameter/Pitch	16 X 21.5
Beam	8' 6"	Displacement	175.0 cu. In.	Number of Blades	3
Weight	2240 lb.s	Operating Range	5500-6100	Mounting Height	
Maximum HP	250	Weight	531 lb.s	Hole Position	#3 Hole Up
Fuel Capacity	47 gallons	Lubrication	Wet Sump	Jack Plate	N/A
Transom Height	20"	Fuel Delivery	Multi-Point EFI		
Steering	Hydraulic	Ignition	Solid State		

PERFORMANCE DATA	TEST CONDITIONS
------------------	-----------------

RPM	MPH	GPH	MPG	RANGE	
IDLE	2.4	0.3	7.83	331	Water Conditions Calm Wind Velocity 5-10mph Air Temperature 86 Fuel Load 27 gal. Weight Onboard 2 person Full Safety Gear
1000	3.9	0.7	5.92	251	
1500	5.8	1.3	4.60	195	
2000	8.1	2.0	4.13	175	
2500	13.7	2.7	5.17	219	
3000	18.2	3.7	4.97	210	
3500	21.9	5.2	4.21	178	
4000	27.1	7.6	3.59	152	
4500	31.7	10.4	3.05	129	
5000	35.9	15.0	2.39	101	
5500	39.9	17.6	2.27	96	
6000	43.6	18.4	2.37	100	

PERFORMANCE SUMMARY	
---------------------	--

Top Speed	43.6 mph
0-25 Acceleration	6.79 seconds
Optimum Cruising Range	@ 2500 RPM 219 Miles
Best Cruising	@ 2500 RPM
Fuel Efficiency	5.17 MPG

Results may vary. Range based on 90% fuel capacity.

FOR MORE INFORMATION, CONTACT:

Silverwave
Seminole, OK
www.silverwavepontoon.com
(405)382-0349

Suzuki Marine
www.suzuki.com

